

moderna[®] vision 8 mm

Technical data sheet · Issue: 03-2008

Product specifications Dimension Content per package Content per pallet Weight per package Weight per pallet (incl. pallet)		vision 8 mm 1380 x 156 x 8 mm 9 pieces (= 1,938 m ²) 60 packages (= 116,28 m ²) 14,2 kg 867 kg
Warranty to wear resistance of the surface Domestic areas Commercial areas		25 years 5 years
Usage / surface features Abrasion class Wear Impact resistant Stain resistant Light fastness Cigarette stain resistant Lift resistant Castor chair effect Shifting a furniture base Impression after constant load Slip resistant Swelling Formaldehyde emission	Standard (EN 13329) (EN 13329) (EN 13329) (EN 13329) (EN ISO 105-B02) (EN 20105-A02) (EN 13329) (EN 13329) (EN 13329) (EN 13329) (EN 13329) (EN 14041) (EN 13329) (EN 717-1)	31 AC4 = IP ≥ 4000 IC 1 Group 1 + 2 = Grade 5 Group 3 = Grade 4 Blue wool scale ≥ 6 Grey scale ≥ 4 Grade 4 ≥ 1,0 N/mm ² no visible changing no visible changing no visible changing Class DS ≤ 8% E1
Physical attributes Thermal resistant Reaction to fire Anti-Static	Requirements (ISO 8302) (EN 13501-1) (EN 14041)	0,062 m ² K/W Cfl-s1 < 2.0 kV
Tolerances Density of HDF core board Squareness of the element Edge straightness Level height Joint change of decor Block effect	Requirements none ≤ 0,20 mm ≤ 0,30 mm average ≤ 0,10 mm maximum ≤ 0,15 mm none none	≥ 900 kg / m ³ ≤ 0,20 mm ≤ 0,30 mm ≤ 0,05 mm ≤ 0,15 mm max. 4 mm min. 80 mm